



omfh332597 - MX8 (S.N. 020000 - )MX10 (S.N. 019000 - )HX10 (S.N. 011500 - )HX14 (S.N. 012510 - )Multi-Spindle Rotary Cutters (N.A. Edition) -: (North American) - MX10 Specifications

**NOTE:**

*Weights are with typical optional equipment. Weight varies with other optional equipment.*

The maximum static vertical load for a pull type cutter occurs in the road transport position when equipped with authorized attachments.

Item	Measurement	Specification
MX10 Maximum Static Vertical Load on Tractor Drawbar	Weight	454 kg (1000 lb.)

-: MX10 Specifications

<b>MANUFACTURER</b>	John Deere
<b>MODEL</b>	MX10
<b>Capacity</b>	
Cutting Width, mm (in.)	3200 (126)
Cutting Height, mm (in.)	25 to 305 (1 to 12)
Cutting Diameter of Material, mm (in.)	50 (2)
Cutting Chamber Depth, mm (in.)	216 (8.5)
<b>Tractor Compatibility</b>	

<b>MANUFACTURER</b>	<b>John Deere</b>
<b>MODEL</b>	<b>MX10</b>
Tractor PTO kW (hp.) Range	Minimum 30 (40) (Pull-Type, Semi-Mount, and Semi-Mount Hydraulic Offset) Minimum 45 (60) (Lift-Type)
Tractor PTO rpm	540
<b>Hitch</b>	
Type	Pull-Type, Lift-type, Semi-mount, Semi-mount Hydraulic offset (Pull-Type has standard 4536 kg ([10 000 lb.] Safety Tow Chain)
Category	2, 3, 3N
<b>Dimensions</b>	
Transport Width, mm (in.)	3280 (129)
Overall Width, mm (in.)	3280 (129)
Overall Length, mm (in.)	4040 (159)
Deck Shape	Domed
Deck Type	Double Deck
<b>Deck Thickness, mm (in.) (gauge)</b>	
—Upper	3 (0.125) (11)
—Lower	3 (0.125) (11)
<b>Side Skirt Thickness, mm (in.) (gauge)</b>	4.5 (0.177) (7)

<b>MANUFACTURER</b>	John Deere
<b>MODEL</b>	MX10
<b>Approximate Weight, kg (lb.)</b>	960 (2113)
<b>Drivelines</b>	
<b>Size</b>	
Main Driveline	ASAE Category 4
Connecting Driveline	—
<b>Protection Type</b>	
Main Driveline	Non-seize, self-adjusting clutch; Pull-Type has equal-angle Category 4 driveline
Connecting Driveline	Shock Absorbing Shafts
<b>Gearcases</b>	
Quantity	3
<b>kW (hp.) Rating</b>	
Transfer Gearcase	89.4 (120) continuous 97 (130) peak
Center Gearcase	—
Outer Gearcase	56 (75) continuous 74.5 (100) peak
<b>Blades</b>	
Thickness, mm (in.)	13 (0.5)

<b>MANUFACTURER</b>	<b>John Deere</b>
<b>MODEL</b>	<b>MX10</b>
Width, mm (in.)	102 (4)
Type	Suction
Overlap, mm (in.)	75 (2.8)
<b>Blade Tip Speed</b>	
540 rpm	82.7 m/s (16 275 fpm)
1000 rpm	—
Material Flow System	Max Flow
Holder	Round Stumpjumper
<b>Wheels</b>	
Type	Laminated (Pull-Type has Severe-Duty Ag tire option)
Row Width Adjustment	Yes - Pull-Type only
<b>Shielding</b>	
Front	Chain
Rear	Chain

Specifications are based on published information at the time of publication. Specifications are subject to change without notice. Contact your local John Deere™ dealer for more information.

*John Deere is a trademark of Deere & Company*

CN80434,00002D1-19-20160525

Copyright © Deere & Company, all rights reserved.